WEST Search History

| Hide Items | Restore | Clear | Cancel |

DATE: Thursday, February 19, 2004

Hide?	Set Name	Query	Hit Count
		DB=USPT; PLUR=YES; OP=ADJ	
☐	L10	L8 near10 word	19
☐	L8	demultiplex$ near3 block	856
		DB=PGPB; PLUR=YES; OP=ADJ	
☐	L7	L6.ab,ti.	8
☐	L6	demultiplex$ near3 block	275
☐	L5	20020095536	1
		DB=USPT; PLUR=YES; OP=ADJ	
☐	L3	demultiplex$ near3 block near10 serial$	30
☐	L2	('5327126')[URPN]	2
☐	L1	5327126.pn.	1

END OF SEARCH HISTORY

First Hit

☐ ⌐ Generate Collection ⌐

L7: Entry 7 of 8   File: PGPB   May 22, 2003

DOCUMENT-IDENTIFIER: US 20030095057 A1
TITLE: Hybrid parallel/serial bus interface

Abstract Paragraph:
A hybrid serial/parallel bus interface has a data block demultiplexing device. The
data block demultiplexing device has an input configured to receive a data block
and demultiplexes the data block into a plurality of nibbles. For each nibble, a
parallel to serial converter converts the nibble into serial data. A line transfers
each nibble's serial data. A serial to parallel converter converts each nibble's
serial data to recover that nibble. A data block reconstruction device combines the
recovered nibbles into the data block.

First Hit

☐   Generate Collection

L7: Entry 6 of 8   File: PGPB   Jun 5, 2003

DOCUMENT-IDENTIFIER: US 20030105893 A1
TITLE: Method employed by a user equipment for transferring data

Abstract Paragraph:
A hybrid serial/parallel bus interface method for a user equipment (UE) has a data
block demultiplexing device. The data block demultiplexing device has an input
configured to receive a data block and demultiplexes the data block into a
plurality of nibbles. For each nibble, a parallel to serial converter converts the
nibble into serial data. A line transfers each nibble's serial data. A serial to
parallel converter converts each nibble's serial data to recover that nibble. A
data block reconstruction device combines the recovered nibbles into the data
block.

First Hit

| Generate Collection |

L7: Entry 5 of 8   File: PGPB   Jun 5, 2003

DOCUMENT-IDENTIFIER: US 20030105894 A1
TITLE: Method employed by a base station for transferring data

Abstract Paragraph:
A hybrid serial/parallel bus interface method for a base station has a data block
demultiplexing device. The data block demultiplexing device has an input configured
to receive a data block and demultiplexes the data block into a plurality of
nibbles. For each nibble, a parallel to serial converter converts the nibble into
serial data. A line transfers each nibble's serial data. A serial to parallel
converter converts each nibble's serial data to recover that nibble. A data block
reconstruction device combines the recovered nibbles into the data block.

First Hit

☐ | Generate Collection |

L7: Entry 4 of 8   File: PGPB   Jun 5, 2003

DOCUMENT-IDENTIFIER: US 20030105895 A1
TITLE: User equipment having a hybrid parallel/serial bus interface

Abstract Paragraph:
A hybrid serial/parallel bus interface for a user equipment (UE) has a data block
demultiplexing device. The data block demultiplexing device has an input configured
to receive a data block and demultiplexes the data block into a plurality of
nibbles. For each nibble, a parallel to serial converter converts the nibble into
serial data. A line transfers each nibble's serial data. A serial to parallel
converter converts each nibble's serial data to recover that nibble. A data block
reconstruction device combines the recovered nibbles into the data block.

First Hit

☐   Generate Collection

L5: Entry 1 of 1   File: PGPB   Jul 18, 2002

DOCUMENT-IDENTIFIER: US 20020095536 A1
TITLE: Parallel read/write circuit and method for efficient storing/retrieval of data to/from a recording medium

Pre-Grant Publication (PGPub) Document Number:
20020095536

First Hit　　Fwd Refs

☐　　Generate Collection

L3: Entry 3 of 30　　　　　　　File: USPT　　　　　　Dec 17, 2002

DOCUMENT-IDENTIFIER: US 6496540 B1
TITLE: Transformation of parallel interface into coded format with preservation of baud-rate

Brief Summary Text (9):
A method of coding parallel data for transmission while maintaining baud rate in accordance with the present invention includes the steps of providing a plurality of uncoded data blocks having a predetermined baud rate, demultiplexing the data blocks to sequentially distribute the data blocks to encoders, encoding the data blocks at the demultiplexed rate and serializing the coded data blocks for serially transmitting data at the predetermined baud rate.